



Switch Mode Power Supply SMPS006

Data sheet

SMPS006

The Switch Mode Power Supply called SMPS006 supplies power to various HOMELINE® or DESKLINE® systems used for applications like leisure beds and basic office desks. With an external power supply, the application becomes a low voltage unit. The SMPS is a universal unit meaning it can be used worldwide. It has an extremely low power consumption in standby mode of only 0.1 W. This is what we call ZERO™ technology.



Features:

- Nominal input voltage (mains voltage): 100 V AC to 240 V AC \pm 10%
- Nominal input: 1.2 A
- Nominal input frequency: 50 Hz / 60 Hz
- Power 175 W
- Standby power consumption of only 0.1 W
- Nominal output voltage: 29 V DC \pm 10%
- Plug type: Mini fit 2-pole
- Colour: Black (RAL 9005)
- Thermal switch

Option:


- Bracket for mounting

Usage:

- Compatible with CBH Advanced, CBD6DC, TD4 Advanced, TD5 Advanced, LA18 IC Advanced, LA10 system, and DESKLINE DL IC systems.
- Can be used as a charger for the BA001 battery
- Storage and transport temperature: -10 to + 70 °C
- Complies with EN60335-1
- Complies with EN61558 and UL 60950-1
- Must follow the duty cycle of the actuator system

Dimensions:

SMPS006



Connection cable: 2-pole cable minifit plug:

Article number	Length	Description
0705839-1350	1350	Angle plug in both ends
CAB0705894-200	200	Straight plug in both ends
CAB0705873-1800	1800	Straight plug in both ends
0705874-1800	1800	Angle plug and straight plug
0705869-3500	3500	Angle plug and straight plug
CAB0705870-3500	3500	Straight plug in both ends

Connection to the mains:

Article number	Length	Description
CAB0015801	3000	Straight mains cable with EU plug
CAB0015827	3000	Straight cable with Japanese plug (PSE-approved)
CAB0015188	3000	Straight cable with US plug


Accessories:

Article number	Description
0705889	Cable locking device for SMPS001/SMPS002/SMPS006
SA0705890	Mounting bracket for SMPS006*

*Must be ordered in quantities of 160 pcs.

Mounting bracket:

A bracket for mounting the SMPS006 onto the application to give a fixed placement and ensure cable relief for the mains cable. Must be ordered separately (SA0705890). The bracket must be fastened with two wood screws with a pan head. The mains cable port of the SMPS006 must face towards the cable relief on the mounting bracket.



LINAK® accepts no responsibility for possible errors or inaccuracies in catalogues, brochures, and other material. LINAK reserves the right to change its products without prior notice. LINAK cannot guarantee product availability and reserves the right to discontinue the sale of any product. The user is responsible for determining the suitability of LINAK products for a specific application. All sales are subject to the 'Standard Terms of Sale and Delivery', available on LINAK websites.

LINAK and the LINAK logotype are registered trademarks of LINAK A/S. All rights reserved.